

Publisher Handbook Account Web Services



Version 1.0

Editor:



belboon-adbutler GmbH
Karl-Liebknecht-Straße 1
10178 Berlin
Germany

Telefon: +49 (0)30 / 72 61 62 -320

FAX: +49 (0)30 / 72 61 62 -311

Internet: www.belboon.de
www.belboon.com
www.belboon.fr
www.belboon.nl

E-Mail: info@belboon.com

Version 1.0

All rights reserved

© belboon-adbutler GmbH 2010

The work including all its parts is copyrighted. Each use outside of the narrow boundaries of the copyright law is inadmissible and punishable without written approval of the belboon-adbutler GmbH. That applies especially to duplication, translation, micro filming and the storage and processing in electronic systems. The utilization within the framework of the cooperation with the belboon-adbutler GmbH is allowed.

The reproduction of names, trademarks, labels etc. in this work does not entitle also without special marking to the acceptance that such names in the sense of the trademark protection and sign protection legislation could be regarded as free and may therefore be used by anybody.

1 Content

1	Content.....	3
2	Introduction.....	4
3	Generating a Web Service Password.....	5
4	Publisher Account Web Services.....	6
4.1	Result Object	6
4.2	Functions.....	7
4.2.1	getAccountInfo	7
4.2.2	getEventList	9

2 Introduction

The belboon Web Services (SOAP-Protokoll) enables you to work with our network automatically without you having to login through the interface.

Web Service-URL: <http://api.belboon.com/?wsdl>

3 Generating a Web Service Password

To use the belboon Web Services you need not login to your belboon account.

In the Menu "Tools & Services > Web Services" you have the opportunity to generate your Web Service password. Afterwards you will be able to see this in this section. The username for the use of the Web Services is exactly the same as the username from your Affiliate account.



The screenshot shows the 'belboon WebService - API' page. On the left is a navigation menu with categories: Werbe Center, Partner, Tools & Services (where 'Webservices' is highlighted), Message Center, Statistik, SmartLinks, and Profil & Finanzen. The main content area shows the 'WebServices' page with a 'Generieren' button. A callout box highlights the 'Freigeschaltet: Ja' and 'WebService Passwort: BWT...' fields. Below this, the 'SmartFeeds-WebService' section lists available API functions like GetPlatforms, GetShops, GetFeeds, GetProductData, GetCategories, and SearchProducts.

4 Publisher Account Web Services

4.1 Result Object

When calling a function of the Web Services, the data will be returned through a single object report. This object contains some metadata, for example: an error message as well as the actual user data.

Result-Object

Index	Type	Description
<code>processor</code>	Object	see below
<code>handler</code>	Object	see below

Processor

Behind the property lies a `processor` object, which stores information about the executed transaction.

Index	Type	Description
<code>code</code>	Integer	Transactions code
<code>message</code>	String	Message according to the transaction codes
<code>rid</code>	Integer	SOAP-Requests ID
<code>testmode</code>	Integer	Provides information on whether the transaction was carried out in test mode.

handler

The property `handler` contains a single property whose name, type and content results on the call up of the web services. This information must in any case be checked again in Section 4.2. The contents of this property are the actual user data.

4.2 Functions

4.2.1 getAccountInfo

Request-Parameter

The operation getAccountInfo() is parameterless.

Response (handler)

Behind the property `handler` of the Result object is hidden again an object with the following publicly visible properties:

Index	Type	Description
customerId	String	belboon customer number
smartRank	Float	belboon SmartRank
inboxMessagesUnread	Integer	Number of unread messages
partnersRecruited	Integer	Number of Partners recruited through the Partner recruits Partner program.
commissionsPending	Array ['programs' => 'smartLinks' => 'compensation' => 'pricecomparison' => 'partnerrecruiting' =>]	List of open commissions, grouped by origin and currency
commissionsApproved	Array [<CURRENCY_1> => ...]	Sum of the confirmed commission grouped by currency

Example:

```
<?php

define('WSDL_SERVER', 'http://api.belboon.com/?wsdl');

// SOAP options (http://de.php.net/manual/de/soapclient.soapclient.php)
$config = array(
    'login' => 'YOUR_LOGIN_NAME',
    'password' => 'YOUR_WEBSERVICE_PASSWORD',
    'trace' => true
);

try {
    $client = new SoapClient(WSDL_SERVER, $config);
    $result = $client->getAccountInfo();

    echo '<pre>';
    print_r($result);
} catch( Exception $e ) {
    // Error handling here...
}
```

4.2.2 getEventList

Request-Parameter

Name	Type	Default	Description
adPlatformIds	Integer[] (Array)	null	One or more IDs of advertising platform (s) to which the query should be limited
programId	Integer	null	Lists only events of the program with this ID
eventType	String {LEAD, SALE}	null	
eventStatus	String {REJECTED, PENDING, APPROVED}	null	
eventCurrency	String	null	
eventDateStart	Date (YYYY-MM-DD)	null	Oldest generation / tracking date of Events
eventDateEnd	Date (YYYY-MM-DD)	null	Latest generation / tracking date of Events
eventChangeDateStart	Date (YYYY-MM-DD)	null	Oldest processing date of Events
eventChangeDateEnd	Date (YYYY-MM-DD)	null	Latest processing date of Events
orderBy	String[] (Array)	array('eventdate' => 'ASC')	Sort the return of the events according to the passed column name with the desired orientation (ASC = ascending, DESC = descending)
limit	Integer	null	Limits the number of results to this max value
offset	Integer	0	Lists results from this value

Response (handler)

Behind the property `handler` lies the Result-object, an object, with a single publicly visible property that bears the name of events. It contains a numerically indexed array of 0 or more rows (arrays), each of which is structured as follows:

Index	Type	Description
<code>eventid</code>	Integer	ID of the Events
<code>programid</code>	Integer	ID of the Partner programs
<code>programname</code>	String	Name of the Partner programs
<code>platformid</code>	Integer	ID of the generated Web platform
<code>platformname</code>	String	Name of the generated Web platform
<code>eventstatus</code>	String {REJECTED, PENDING, APPROVED}	
<code>eventdate</code>	DateTime (YYYY-MM-DD hh:mm:ss)	Generation/Tracking date of the Events
<code>lastchangedate</code>	DateTime (YYYY-MM-DD hh:mm:ss)	Date of the last processing of Events
<code>eventtype</code>	String {LEAD, SALE}	Event Type
<code>ordercode</code>	String	Advertisers Order Code
<code>eventcurrency</code>	String	Currency of the Events
<code>eventcommission</code>	Float	Commission in Event Currency
<code>eventcondition</code>	String	Commission group of the Events
<code>netvalue</code>	Float	Net goods value of the order
<code>eventinfo</code>	String	Cancellation reason or part cancellation information
<code>subid</code>	String	SubId Information

Example:

```
<?php
define('WSDL_SERVER', 'http://api.belboon.com/?wsdl');

// SOAP options (http://de.php.net/manual/de/soapclient.soapclient.php)
$config = array(
    'login' => 'YOUR_LOGIN_NAME',
    'password' => 'YOUR_WEBSERVICE_PASSWORD',
    'trace' => true
);

try {
    $client = new SoapClient(WSDL_SERVER, $config);
    $result = $client->getEventList(
        null, // adPlatformIds
        null, // programId
        'SALE', // eventType
        'PENDING', // eventStatus
        'EUR', // eventCurrency
        date('Y-m') . '-01', // eventDateStart
        null, // eventDateEnd
        null, // eventChangeDateStart
        null, // eventChangeDateEnd
        array('platformname' => 'ASC'), // orderBy
        25, // limit
        0 // offset
    );

    echo '<pre>';
    print_r($result);
} catch( Exception $e ) {
    // Error handling here...
}
```



belboon-adbutler GmbH

Karl-Liebknecht-Straße 1
10178 Berlin
Germany

USt-IdNr: DE 2207 19614
Amtsgericht Berlin (Charlottenburg) - HRB 125210
Managing Director: Manuel Kester

Tel: +49 (0)30 / 72 61 62 -320

FAX: +49 (0)30 / 72 61 62 -311

Internet: www.belboon.de
www.belboon.com
www.belboon.fr
www.belboon.nl

E-Mail: info@belboon.com